



ABC LIOVIN



# CME 75HT

## KEY SPECS

- Width - 8' 2"
- Length - 22' 4"
- Folded Height - 10' 4"
- Mast-Up - 29'
- Retract/Down Pressure 30,000 lbs/20,000 lbs
- Rotary Torque - 13,000 ft/lbs

## LEARN MORE

[info@abcdrilling.com](mailto:info@abcdrilling.com)

Phone: + 1 (562) 9818575

Web: [abcdrilling.com](http://abcdrilling.com)

This rig has plenty of torque to get down to depths up to 150'. The Peterbilt carrier has a short wheelbase, ideal for maneuvering around tight jobsites.

## CAPABILITIES

- Hollow Stem Auger/Mud/Air/Rotary/Wireline Coring Drill Rig
- 72" stroke, hydraulic vertical drive system
- Retract rate up to 78 ft/min with Fine Hydraulic Feed Control for controlling feed and pressure.
- Moyno 3L8 water/pump with high/low gearing
- Coated 500 Gallon Water Tank
- Hydraulic Auger Rack capable of carrying 130' of 4 1/4" ID or 60' of 6 1/4" ID Augers
- Three hydraulic leveling jacks for stability during drilling
- Four total winches: Two auxiliary winch lines, one main line and one fast wireline for sampling.
- Calibrated above ground SPT auto-hammer for geotechnical sampling.
- Decon Trailer with steam cleaner for decontaminating downhole tooling