



ABC LIOVIN



CME 85

KEY SPECS

- Width - 8' 4"
- Length - 31'
- Folded Height - 11' 10"
- Mast-Up - 35' 6"
- Retract/Down Pressure 48,000 lbs/28,000 lbs
- Rotary Torque - 23,000 ft/lbs

LEARN MORE

info@abcdrilling.com

Phone: + 1 (562) 9818575

Web: abcdrilling.com

This rig is brute force, capable of getting down to 200' and beyond through cobbles and tough conglomerates. It's equipped with a robust frame, and rotary drive as well as an angle package.

CAPABILITIES

- Hollow Stem Auger/Mud/Air/Rotary/Wireline Coring Drill Rig
- 72" stroke, hydraulic vertical drive system
- Retract rate up to 78 ft/min with Fine Hydraulic Feed Control for controlling feed and pressure.
- Two isolated controls for manual control without changing pressure settings with detent.
- Angle drilling capabilities
- Five forward gears and one reverse with heavy-duty 13 inch clutch
- Moyno 3L8 & 435 Bean water/mud pump with high/low gearing
- Coated 500 Gallon Water Tank
- Hydraulic Auger Rack capable of carrying 130' of 4 1/4" ID or 60' of 6 1/4" ID Augers
- Three hydraulic leveling jacks for stability during drilling
- Four total winches: Two auxiliary winch lines, one main line and one fast wireline for sampling.
- Calibrated above ground SPT auto-hammer for geotechnical sampling.
- Decon Trailer with steam cleaner for decontaminating downhole tooling