



ABC LIOVIN



High Torque Rubber Track Mounted Limited Access Rig with a Built Frame to Support Deeper Drilling Efforts.

Limited Access Rig

KEY SPECS

- Rig weight: approximately 14,000 lbs
- Rig width: 6' 6"
- Rig height mast down: 8'
- Rig height mast up fully retracted 12' 6"
- Rig height mast up fully extended 18'
- Hollow Stem Auger/Mud/Air Rotary Capabilities

LEARN MORE

info@abcdrilling.com

Phone: + 1 (562) 9818575

Web: abcdrilling.com

CAPABILITIES

- Heavy duty tower and frame built for extreme drilling conditions.
- Capable of spinning up to 18" OD Hollow Stem Augers.
- High Powered Cummins Diesel Capable of turning auger in excess of 200' bgs.
- More pullback than most truck mounted drill rigs.
- Hydraulic telescoping tower capable of drilling under 12'6" and extending up to 18'.
- Four hydraulic leveling jacks for stabilizing rig on uneven surfaces.
- Air compressor on rig allows for use of air tools and for pressure grouting.
- Two coated 75 gallon water tanks and Moyno 3L6 water pump mounted on rig.
- Auger rack capable of holding up to 60 ft of 4 1/4" ID augers.
- Automatic hammer and wireline slide hammer sampling capabilities.
- Separated drill/rubber track controls for added safety.
- Small footprint ideal for active sites.
- High temperature exhaust tubing and fans available for indoor work.